

S 8

S 10



S 8 i



S 10 i

S 8 Ecoline  
S 10 Ecoline

NEW



optional: CONTROL B+Touch

## Technische Daten / Technical data

|  | S 8              | S 8 Ecoline     | S 10             | S 10 ecoline     |
|--|------------------|-----------------|------------------|------------------|
| Presskraft (kN/Ton) / Crimp Force  | 2200 / 220       | 2200 / 220      | 2800 / 280       | 2800 / 280       |
| Schmierung entfällt: 20% weniger Reibung<br>No Grease: 20% less friction | ✓                | ✓               | ✓                | ✓                |
| Steuerung / Control  | Control A        | Mikrometer      | Control A        | Control A        |
| SAE R 15 / 4SH* 1 Teil Armatur / 1 piece                                 | 2"               | 2"              | 2"               | 2"               |
| 4SH* 2 Teil Armatur / 2 piece  | 2"               | 2"              | 2"               | 2"               |
| SAE R 15* 2 Teil Armatur / 2 piece                                       | 1 1/2"           | 1 1/2"          | 2"               | 2"               |
| Industrie / Industrial   | 4"               | 4"              | 4"               | 4"               |
| 90° Bogen / Elbows   | 2"               | 2"              | 2"               | 2"               |
| Max. Pressbereich / Crimp range  | 139 mm           | 139 mm          | 139 mm           | 139 mm           |
| Öffnungsweg / Opening  | + 45 mm          | + 45 mm         | + 45 mm          | + 45 mm          |
| Öffnung ohne Backen /<br>Opening without dies                            | 190 mm           | 190 mm          | 190 mm           | 190 mm           |
| Backentyp / Type of dies   | 239 L / 237 L**  | 239 L / 237 L** | 239 L / 237 L**  | 239 L / 237 L**  |
| Geschwindigkeit (mm/sec.) / Speed  |                  |                 |                  |                  |
| Schliessen / Close   | 6,1              | 5,8             | 6,1              | 6,1              |
| Pressen / Crimp  | 1,7              | 2,5             | 1,7              | 1,7              |
| Öffnen / Open  | 10,3             | 9,0             | 10,3             | 10,3             |
| Geräuschpegel / Noise level  | 63 dBA           | 63 dBA          | 63 dBA           | 63 dBA           |
| Antrieb / Drive  | 4 kW             | 4 kW            | 5,5 kW           | 5,5 kW           |
| Öl / Oil   | 55 l             | 50 l            | 55 l             | 50 l             |
| L x B x H (mm) / L x W x H   | 690 x 600 x 1400 | 693 x 600 x 840 | 690 x 600 x 1400 | 690 x 600 x 1400 |
| Gewicht / Weight   | 390 kg           | 372 kg          | 390 kg           | 390 kg           |

S 8 / S 10 Paket / Package = Maschine / Machine + PB Ø 17, 20, 24, 28, 32, 40, 44, 50, 57, 71 + 237.239.2L2

## Optional



## Paket / Package



\* Abhängig von der Armatur / According to the fitting  
 \*\* ohne Zwischenbacken / Intermediate dies not required  
 \*\*\* nur mit Control B+ Touch

Backentyp  
Type of dies

239 L

237 L\*\*

| Ø mm | -mm- | -mm- |
|------|------|------|
| 6,8  | 40   |      |
| 9    | 70   |      |
| 12   | 70   |      |
| 14   | 70   |      |
| 16   | 70   |      |
| 17   | 70   |      |
| 19   | 70   |      |
| 20   | 70   |      |
| 22   | 70   |      |
| 24   | 70   |      |
| 26   | 70   |      |
| 28   | 85   |      |
| 32   | 85   |      |
| 36   | 85   |      |
| 40   | 85   |      |
| 44   | 85   |      |
| 47   | 110  |      |
| 50   | 110  |      |
| 54   | 110  | 118  |
| 57   | 110  | 118  |
| 62   | 110  | 118  |
| 67   |      | 118  |
| 71   |      | 118  |
| 74   |      | 118  |
| 78   |      | 118  |
| 84   |      | 118  |
| 86   |      | 118  |
| 90   |      | 118  |
| 96   |      | 118  |
| 103  |      | 118  |
| 106  |      | 126  |
| 111  |      | 126  |
| 116  |      | 126  |
| 121  |      | 126  |
| 126  |      | 126  |
| 131  |      | 126  |

Technische Änderungen vorbehalten. / We reserve the right to make technical changes without notice.